

5722-XH2 V5R3 iSeries Access for Web

WebSphere Application Server V6.0 for OS/400 (“Base and Express Editions”) - Setup/Configuration Example

First Edition (February 2005)

This edition supplements the V5R3 iSeries Access for Web InfoCenter documentation.

(C) Copyright International Business Machines Corporation 1999, 2005. All rights reserved.
U.S. Government Users Restricted Rights -- Use, duplication or disclosure restricted by GSA ADP
Schedule Contract with IBM Corp.

Contents

[About this information](#)

[General information](#)

[Getting Started](#)

[License Information](#)

[Overview](#)

[Deploying iSeries Access for Web](#)

[Creating and Starting an HTTP server and Web application server](#)

[Configuring iSeries Access for Web to run in the web application server](#)

[iSeries Access for Web commands](#)

[Additional information](#)

[IBM HTTP Server for iSeries](#)

[WebSphere Application Server V6.0 for OS/400 iSeries](#)

[iSeries Access for Web](#)

About this information

The information in this document is a supplement to the information available in the IBM iSeries InfoCenter documentation.

The V5R3 iSeries Access for Web InfoCenter documentation is available in various language translations from the iSeries Access for Web website:

<http://www.ibm.com/servers/eserver/iseries/access/web/>

The V5R3 iSeries Access for Web InfoCenter documentation covers topics such as:

- Licensing information
- An installation/setup checklist that addresses:

- Hardware/Software/web browser requirements.
- Installation of iSeries Access for Web to the iSeries server.
- Verification of PTFs.
- Configuration of iSeries Access for Web for the web environment on the iSeries server.
- Using iSeries Access for Web
- Administration and customization of iSeries Access for Web

iSeries Access for Web support for WebSphere Application Server V6.0 for OS/400 was added after the V5R3 iSeries Access for Web InfoCenter documentation was written so the InfoCenter documentation does not specifically address the WebSphere V6.0 environment. This document was written to supplement the InfoCenter documentation.

This document assumes you have been using the setup checklist in Chapter 4 of the iSeries Access for Web InfoCenter documentation. The checklist steps #8 and #10 should have pointed you to this document for an example of:

- Creating and Starting HTTP servers and Web application servers
- Configuring iSeries Access for Web to run in the web application server.

If you have not been using the setup checklist in Chapter 4 of the iSeries Access for Web InfoCenter documentation, you should refer to that documentation before continuing with the information below.

General information

- You should read this information if you want to learn how to deploy iSeries Access for Web servlets to the WebSphere Application Server V6.0 for OS/400 web environment.
- This information assumes that the system administrator will install and configure the iSeries server.
- In order to configure the iSeries server, you need a security level of Security Officer (*SECOFR). This is the highest level of security on the iSeries server.
- Familiarity with the iSeries server is strongly recommended.
- Familiarity with the iSeries server web-serving environment is strongly recommended.
- Installation and configuration is necessary only on the iSeries server. Workstations only require a connection to the iSeries server and a web browser.
- V5R3 iSeries Access for Web requires V5R2 and later OS/400 iSeries servers.
- The example information in this document assumes the latest PTFs have been loaded and applied for the following and their dependent software products:
 - 5722-DG1 IBM HTTP Server for iSeries
 - 5733-W60 IBM WebSphere Application Server V6.0 of OS/400

Getting Started

License Information

iSeries Access for Web is a licensed program product. All components of iSeries Access for Web require an iSeries Access (5722-XW1) license before you can use them.

For more information, refer to the V5R3 iSeries Access for Web InfoCenter documentation which is

available in various language translations from the iSeries Access for Web website:
<http://www.ibm.com/servers/eserver/series/access/web/>

Overview

This document assumes you have been using the setup checklist in Chapter 4 of the iSeries Access for Web InfoCenter documentation. The checklist steps #8 and #10 should have pointed you to this document for an example of:

- Creating and Starting HTTP servers and Web application servers
- Configuring iSeries Access for Web to run in the web application server.

If you have not been using the setup checklist in Chapter 4 of the iSeries Access for Web InfoCenter documentation, you should refer to that documentation before continuing with the information below.

To begin using iSeries Access for Web servlets, the servlet web environment must be setup on the iSeries server. The sections below provide an example of how to set up the servlet web environment and configure iSeries Access for Web for that environment.

Deploying iSeries Access for Web

The information below will guide you through the process of creating a WebSphere web application server, an HTTP web server, and configuring iSeries Access for this new web environment.

The configuration instructions documented below are only an example. You may modify the configuration values if you wish. If you are unfamiliar with the web serving environment, it is highly recommended that you use the configuration values documented below. As you become more experienced with the web environment on your iSeries server, you can create additional web serving environments where you can modify the configuration values.

Follow the sections in the order outlined below.

Creating and Starting an HTTP server and Web application server

The instructions below assume steps 1 – 7 of the setup checklist in Chapter 4 of the iSeries Access for Web InfoCenter documentation have been completed. If you have not completed steps 1 – 7, it is highly recommended that those steps be completed before continuing with the information below.

The instructions below assume the latest PTFs have been loaded and applied to the iSeries server for the following software products:

- 5722-DG1 IBM HTTP server for iSeries
(<http://www.ibm.com/servers/eserver/series/software/http/>)
- 5733-W60 WebSphere Application Server V6.0 for OS/400
(<http://www.ibm.com/servers/eserver/series/software/websphere/wsappserver/>)

Use the instructions below to create a WebSphere instance/application server and HTTP web server.

1. Sign on to a 5250 session. The user profile you use must have security officer authority.
2. Run the server command:
STRTCPSVR *HTTP HTTPSVR(*ADMIN)
3. Open a web browser to:
http://<server_name>:2001
4. Click the link:
IBM HTTP Server for iSeries or IBM Web Administration for iSeries
5. Click the tab labeled:
Setup
6. Under “Common Tasks and Wizards”, click the link labeled:
Create Application Server
7. The screen will be refreshed. On the Create Application Server page, click the button:
Next
8. The screen will be refreshed. On the Select WebSphere Application Server Version page, select the radio button for:
V6.0
9. Click the button:
Next
10. On the Specify Application Server Name page, type the following exactly as shown in the Application server name field:
iwa60
11. Click the button:
Next
12. On the Select HTTP Server Type page, select the radio button for:
Create a new HTTP server (powered by Apache)
13. Click the button:
Next
14. On the Create a new HTTP server (powered by Apache) page, type the following in the HTTP server name field:
iwa60

(Note: We are using the same name for both the WebSphere profile/application server and the HTTP server so that it is easy to see that the two servers are associated with each other. It is OK to use the same name for each because they are two different types of servers running in different subsystems.)
15. Type the following in the Port field:

2046

(Note: Please verify that port 2046 is available for use. Use the NETSTAT *CNN server command to list ports that are currently in use on your server. Check the listed ports to verify 2046 is not already being used by some other program. If 2046 is already being used, specify a different value for this field.)

16. Click the button:

Next

17. On the Specify Internal Ports Used by the Application Server page, the First port in range field has been defaulted to a port number. The wizard has verified the default value is available for use. Do not change the default value unless you are sure the value you type is available for use.

18. Click the button:

Next

19. On the Select Business and Sample Applications page, do not change any of the default selections unless you are sure you need or desire to have those applications installed.

20. Click the button:

Next

21. If the Configure Identity Token SSO for Web to i5/OS Access page is displayed, select the radio button for:

Do not configure Identity Tokens

Click the button: **Next**

22. On the Summary page, click the button:

Finish

23. The page will be refreshed showing that your web environment is being created. Wait for the create step to complete before continuing. When the create step completes, the status will be updated to Stopped.

Congratulations, you have successfully created a WebSphere profile/application server named **iwa60** and an HTTP server named **IWA60**.

Configuring iSeries Access for Web to run in the web application server

The instructions below assume steps 1 – 9 of the setup checklist in Chapter 4 of the iSeries Access for Web InfoCenter documentation have been completed. If you have not completed steps 1 – 9, it is highly recommended that those steps be completed before continuing with the information below.

The instructions below assume a WebSphere Application Server V6.0 for OS/400 profile/application server has been created on the iSeries server (see above for an example).

The instructions below assume the latest PTF(s) for the following software product(s) have been loaded

and applied to the iSeries server:

- V5R3 5722-XH2 iSeries Access for Web
(<http://www.ibm.com/servers/eserver/series/access/web/>)

iSeries Access for Web provides a script command that is run within the Qshell environment to deploy the servlets. Use the steps below to run the command:

1. Sign on to a 5250 session. The user profile you use must have *ALLOBJ special authority.
2. The WebSphere application server must be running before iSeries Access for Web can be configured. Run the server command:
STRTCPSVR *HTTP HTTPSVR(*ADMIN)
3. Open a web browser to:
http://<server_name>:2001
4. Click the link:
IBM HTTP Server for iSeries or IBM Web Administration for iSeries
5. Click the tab labeled:
Manage
6. Click the sub-tab labeled:
Application Servers
7. In the Server dropdown dialog, select:
iwa60/iwa60 – V6.0
8. In the upper left of the page, click the link to Start the profile/application server. The status will be updated to Starting. Wait for the status to be updated to Running before continuing to the next step.
9. Return to the 5250 session.
10. Run the server command:
DSPPTF 5722XH2
11. Verify the following PTF is listed as having a status of applied or superseded.
SI16754
12. Run the server command:
QSH
13. Run the server command:
cd /QIBM/ProdData/Access/Web2/install
14. Run the server command exactly as shown:
cfgaccweb2 –appsvrtype *WAS60 –wasprf iwa60 –appsvr iwa60
15. As the command runs, several messages will be displayed:

*Configuring iSeries Access for Web**Preparing to perform the configuration changes.**Calling WebSphere to perform the configuration changes.**iSeries Access for Web command has completed.**The WebSphere instance application server must be stopped and then started to enable the configuration changes.*

16. When the command completes, iSeries Access for Web has been configured. To enable the configuration change, the WebSphere profile/application server must be restarted. The remaining steps help you restart the profile/application server.
17. Return to the browser session. In the upper left of the page, click the link to Stop the profile/application server. The status will be updated to Stopping. Wait for the status to be updated to Stopped before continuing to the next step
18. In the upper left of the page, click the link to Start the profile/application server. The status will be updated to Starting. Wait for the status to be updated to Running before continuing to the next step.
19. At the top of the web page, select the sub-tab labeled:
HTTP Servers
20. In the Server dropdown dialog, select:
IWA60 - Apache
21. In the upper left of the page, click the link to Start the HTTP server. Wait for the status to be updated to Running before continuing to the next step.
22. Open a new browser session to:
http://<server_name>:2046/webaccess/iWAHome

(Note: If 2046 was substituted with a different port number when the web environment was created, you should use that port number in the above browser address.)

Additional Information:**Errors/Unexpected results**

If an error were to occur with the `cfgaccweb2` command, the following log files are the first place to get additional information. If you place a call to IBM Software Service, they will ask that you provide these files:

- /QIBM/UserData/Access/Web2/logs/cmds.log
- /QIBM/UserData/Access/Web2/logs/cmdstrace.log
- /QIBM/UserData/Access/Web2/was60/iwa60/iwa60/logs/*.log

rmvaccweb2 command

The `rmvaccweb2` command can be used to remove the iSeries Access for Web configuration. The command can be found in the same location as the `cfgaccweb2` command and it would be invoked with the same parameters: **`rmvaccweb2 -appsvrtype *WAS60 -wasprf iwa60 -appsvr iwa60`**

iSeries Access for Web commands

The iSeries Access for Web commands used for the WebSphere Application Server V6.0 for OS/400 are script commands run within the QShell environment. Script commands were provided because support for this environment was added to the product in a PTF. The CL commands that are used for other web environments could not be updated and delivered in a PTF, so script commands were provided.

The example documentation above only mentioned two of the iSeries Access for Web commands, and just a few parameters for those commands.

The complete list of commands include:

- `cfgaccweb2` Configure iSeries Access for Web
- `straccweb2` Start iSeries Access for Web
- `endaccweb2` End iSeries Access for Web
- `rmvaccweb2` Remove iSeries Access for Web

For additional information on these commands and how to use them for the WebSphere Application Server V6.0 for OS/400, you can use the online help that is available with the CL commands. The CL commands support the WebSphere Application Server V5.0 for iSeries Environment. The parameters for the WebSphere V5.0 and V6.0 environments are essentially the same so the help available in the CL commands can be referenced when using the script commands.

To access the help:

1. Sign on to a 5250 session.
2. Type one of the following commands (do not press Enter):
 - `QIWA2/CFGACCWEB2 APPSVRTYPE (*WAS50)`
 - `QIWA2/STRACCWEB2 APPSVRTYPE (*WAS50)`
 - `QIWA2/ENDACCWEB2 APPSVRTYPE (*WAS50)`
 - `QIWA2/RMVACCWEB2 APPSVRTYPE (*WAS50)`
3. Press the F1 key to display all the help for the command. Press F3 before continuing to the next step.
4. Press the F4 key to prompt the command and see what parameters are available.

Note: WASINST will be displayed as a parameter. For WebSphere Application Server V6.0 for OS/400, WASINST is not a valid parameter. Where WASINST is displayed/referenced you should assume that the parameter `-wasprf` would be used with the script command.

5. Use the F1 key on the individual parameters for additional information on that specific parameter.
6. Press the F11 key to display the keywords for the individual parameters. The parameter keywords are displayed in uppercase. Those same keywords can be used with the script command. For example:

The CL command for WebSphere 5.0 might be invoked like this:

```
QIWA2/CFGACCWEB2 APPSVRTYPE(*WAS50) WASINST(my_wasinst) APPSVR(my_appsvr)  
NODENAME(my_nodename)
```

The script command for WebSphere 6.0 would be invoked like this:

```
cfgaccweb2 -appsvrtype *WAS60 -wasprf my_wasprf -appsvr my_appsvr
```

Additional information

IBM HTTP Server for iSeries

For additional information on the IBM HTTP Server for iSeries, refer to the following web site:

<http://www.ibm.com/servers/eserver/series/software/http/>

WebSphere Application Server V6.0 for OS/400

For additional information on WebSphere Application Server V6.0 for OS/400, refer to the following web site:

<http://www.ibm.com/servers/eserver/series/software/websphere/wsappserver/>

iSeries Access for Web

For additional information on iSeries Access for Web, refer to the following website:

<http://www.ibm.com/servers/eserver/series/access/web/>
